


# 200W Single Output with PFC Function



- Universal AC input / Full range
- PF>0.98@115VAC; >0.93@230VAC
- Protections: Short circuit / Overload / Over voltage / Over temp.
- Built-in fan speed control
- Remote ON/OFF control (option)
- Forced air cooling by built-in DC fan
- Approvals: UL / CUL / TUV / CB / CE / S-MARK
- 3 years warranty



CASE: 916B

199x 99x 50 mm

AC input voltage range..... 85~264VAC; 120~370VDC  
 DC adjustment range ..... -5~+10% rated output voltage  
 Overload protection ..... 105%~150% constant current, auto-recovery  
 Over voltage protection ..... 110%~135% rated output voltage  
 Withstand voltage..... I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1minute  
 Working temperature ..... -10~60°C(refer to output derating curve)  
 Safety standards..... UL60950-1, TUV EN60950-1, J60950 approved  
 EMC standards..... EN55022 class B, EN61000-3-2,3  
 EN61000-4-2,3,4,5,6,8,11, ENV50204  
 Connection ..... 7P/ 9.5mm pitch terminal block with cover  
 Packing ..... 0.85kg ; 20pcs / 17.9kg / 1.28CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
10401	SP-200-3.3	3.3V, 0~40.0A	±2%	100mV	65%
10402	SP-200-5	5V, 0~40.0A	±2%	100mV	71%
10403	SP-200-7.5	7.5V, 0~26.7A	±2%	100mV	76%
10404	SP-200-12	12V, 0~16.7A	±2%	100mV	79%
10405	SP-200-13.5	13.5V, 0~14.9A	±2%	100mV	80%
10406	SP-200-15	15V, 0~13.4A	±2%	100mV	81%
10407	SP-200-24	24V, 0~8.40A	±1%	150mV	83%
10408	SP-200-27	27V, 0~7.50A	±1%	150mV	83%
10409	SP-200-48	48V, 0~4.20A	±1%	250mV	84%